

# Grapple Root Rake



## Features



- 53" Clam Opening
- Replaceable Tips on Bucket Teeth
- Concrete Removal
- Brush Removal
- Demolition Clean-up
- Rock Removal
- Guards for Cylinders
- Spring Loaded Hose Guide to help protect hoses from damage

*The Grapple Root Rake helps with site clean up of brush, rocks, stumps and demolition material.*

*The Grapple Root Rake is an ideal attachment for removing debris and leaving the soil behind.*

**Skid Loader Attachments**



# Grapple Root Rake

## Specifications

Model	RTG76	RTG84
Overall Bucket Width	78"	86.5"
Overall Bucket Depth	28"	28"
Height of Bucket Back	39.5"	39.5"
Overall Height w/ Grapple Closed	39.5"	39.5"
Overall Height w/ Grapple Open	59"	59"
Overall Grapple Clam Width	73"	81.5"
Grapple Clam Opening	53"	53"
Bucket Tooth Material	3/4" Thick T-1	3/4" Thick T-1
Grapple Tooth Material	1/2" Gr. 50	1/2" Gr. 50
Bucket Tooth Spacing	8"	8"
Number of Bucket Teeth	10	11
Replaceable Tooth Tips	10	11
Approx. Weight of Bucket	1330	1456#
<b>Hydraulic Cylinder Specifications</b>		
Number of Hydraulic Cylinders	2	2
Bore	3"	3"
Stroke	10"	10"
Rod Diameter	1.5"	1.5"
Cylinder Pressure Rating	3500 PSI	3500 PSI
Hydraulic Hose Rating 4800 PSI		
Nylon Sleeves Protector on Hydraulic Hoses		

Your TMW Dealer



**Attachments**  
320-453-3525

522 Meeker Ave. E. • Eden Valley, MN 55329